



## Technical Specification

LXR3799PSBM - 1 Gang 20A DP Switch with Flex Outlet & Neon



### General

**Box quantity:** 1  
**GTIN-13 / EAN:** 5056199054688  
**Total gross weight (g) includes packing:** 162.00  
**Total net weight (g) excluding packaging:** 157.00  
**Individual unit weight (g):** 157.00  
**Width mm:** 85.00  
**Height mm:** 85.00  
**Depth mm:** 20.00  
**Size/Dimensions (mm):** 85X85X20  
**Surf area M<sup>2</sup>:** 0.021

### Technical

**ABC indicator:** B  
**Insert colour:** black  
**Face plate finish:** polished steel  
**Rocker finish:** polished steel  
**With indicator lamp:** yes  
**Number of rockers:** 1  
**Associated standards:** BS EN 60669-1  
**Rated voltage:** 220-250V  
**Rated current:** 20A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 3 x 1.5mm 2 x 2.5mm 1 x 4.0mm  
**Face plate material:** high grade stainless steel  
**Minimum wall box depth:** 35  
**Nature of supply:** AC  
**Fixing screws:** 2 x M3.5