CONTACTUM

Technical Specification

LYR3787BSW - 1 Gang 32A DP Switch Neon White



General

Box quantity: 1

Total gross weight (g) includes packing: 157.00 Total net weight (g) excluding packaging: 152.00

Individual unit weight (g): 152.00

Width mm: 85.00 Height mm: 85.00 Depth mm: 30.00

Size/Dimensions (mm): 85X85X30

Surf area M^2: 0.025

Technical

ABC indicator: B **Insert colour:** white

Face plate finish: brushed steel Rocker finish: white moulded With indicator lamp: yes Number of rockers: 1

Associated standards: BS EN 60669-1

Rated voltage: 220-250V Rated current: 32A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

 $\begin{tabular}{ll} \textbf{Terminal capacity:} & 3 \times 1.5 mm \ 2 \times 2.5 mm \ 1 \times 4.0 mm \\ \textbf{Face plate material:} & high grade stainless steel \\ \end{tabular}$

Surface protection: lacquered Minimum wall box depth: 35

Nature of supply: AC Fixing screws: 2 x M3.5

