



Technical Specification

LYR6346BSWM - 1 Gang 13A DP Switched Socket Brushed Steel White Insert Metal Rocker + USB 5v/2100mA



General

Box quantity: 1

GTIN-13 / EAN: 5056199054947

Total gross weight (g) includes packing: 194.00

Total net weight (g) excluding packaging: 189.00

Individual unit weight (g): 189.00

Width mm: 85.00

Height mm: 85.00

Depth mm: 30.00

Size/Dimensions (mm): 85X85X30

Surf area M²: 0.025

Technical

ABC indicator: A

Insert colour: white

Face plate finish: brushed steel

Rocker finish: brushed steel

Number of rockers: 1

Number of outlets: 1

Number of socket outlets switchable: 1

Associated standards: BS 1363-2 2016+A1:2018

Rated voltage: 220-250V

Rated current: 13A

Frequency: 50-60Hz

Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

With built-in USB power supply: yes

Terminal capacity: 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm

Face plate material: high grade stainless steel

Surface protection: lacquered

Minimum wall box depth: 35

Nature of supply: AC

Fixing screws: 2 x M3.5