
CONTACTUM



Technical Specification

LYR6356BBBM - 2 Gang 13A DP Switched Socket Brushed Brass Black Insert Metal Rocker + USB 5v/4800mA



General

Box quantity: 1

GTIN-13 / EAN: 5056199055043

Total gross weight (g) includes packing: 329.00 Total net weight (g) excluding packaging: 322.00

Individual unit weight (g): 322.00

Width mm: 145.00 Height mm: 85.00 Depth mm: 30.00

Size/Dimensions (mm): 145X85X30

Surf area M^2: 0.038

Technical

ABC indicator: B Insert colour: black

Face plate finish: brushed brass Rocker finish: brushed brass Number of rockers: 2 Number of outlets: 2

Number of socket outlets switchable: 2 Associated standards: BS 1363-2 2016+A1:2018

Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole

Min. switch contact gap: 3mm

Ambient operating temperature:

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

With built-in USB power supply: yes

Terminal capacity: 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm **Face plate material:** high grade electro plated stainless steel

Surface protection: lacquered Minimum wall box depth: 35

Nature of supply: AC Fixing screws: 2 x M3.5

