



## Technical Specification

CLA4900M - 2 Gang 13A Latching Socket DP



### General

**Box quantity:** 1  
**GTIN-13 / EAN:** 5056199015153  
**Total gross weight (g) includes packing:** 561.00  
**Total net weight (g) excluding packaging:** 503.00  
**Individual unit weight (g):** 503.00  
**Width mm:** 140.00  
**Height mm:** 80.00  
**Depth mm:** 45.00  
**Size/Dimensions (mm):** 140X80X45  
**Surf area M<sup>2</sup>:** 0.042

### Technical

**ABC indicator:** A  
**Insert colour:** white  
**Fault current protection (RCD):** 30mA  
**Face plate finish:** metal  
**Rocker finish:** white moulded  
**Number of rockers:** 2  
**Number of outlets:** 2  
**Number of socket outlets switchable:** 2  
**Associated standards:**  
BS7288: 2016 & BS 1363-2: 2016 +A1: 2018  
**Rated voltage:** 220-250V  
**Rated current:** 13A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm  
**Face plate material:** steel  
**Nature of supply:** AC  
**Rated fault current:** 30mA  
**Fixing screws:** 2 x M3.5  
**Mounting method:** surface

**RCD Type:** Type A