



Technical Specification

CLA4900M - 2 Gang 13A Latching Socket DP



General

Box quantity: 1
GTIN-13 / EAN: 5056199015153
Total gross weight (g) includes packing: 561.00
Total net weight (g) excluding packaging: 503.00
Individual unit weight (g): 503.00
Width mm: 140.00
Height mm: 80.00
Depth mm: 45.00
Size/Dimensions (mm): 140X80X45
Surf area M²: 0.042

Technical

ABC indicator: A
Insert colour: white
Fault current protection (RCD): 30mA
Face plate finish: metal
Rocker finish: white moulded
Number of rockers: 2
Number of outlets: 2
Number of socket outlets switchable: 2
Associated standards:
BS7288: 2016 & BS 1363-2: 2016 +A1: 2018
Rated voltage: 220-250V
Rated current: 13A
Frequency: 50-60Hz
Wiring system: 2 pole
Min. switch contact gap: 3mm
Ambient operating temperature:
-5 to 40°C (24hour average not exceeding 25°C)
Degree of protection: IP2X
Terminal capacity: 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm
Face plate material: steel
Nature of supply: AC
Rated fault current: 30mA
Fixing screws: 2 x M3.5
Mounting method: surface

RCD Type: Type A