



## Technical Specification

ALF4900WHW - 13A 2G DP Switch Skt RCD 30mA (Latching)



### General

**Box quantity:** 1  
**Total gross weight (g) includes packing:** 287.00  
**Total net weight (g) excluding packaging:** 213.00  
**Individual unit weight (g):** 213.00  
**Width mm:** 147.00  
**Height mm:** 95.00  
**Depth mm:** 40.00  
**Size/Dimensions (mm):** 147X95X40  
**Surf area M<sup>2</sup>:** 0.047

### Technical

**ABC indicator:** A  
**Colour:** White  
**Insert colour:** white  
**Face plate finish:** moulded  
**Rocker finish:** white moulded  
**Number of rockers:** 2  
**Number of outlets:** 2  
**Number of socket outlets switchable:** 2  
**Associated standards:**  
BS7288: 2016 & BS 1363-2: 2016 +A1: 2018  
**Rated voltage:** 220-250V  
**Rated current:** 13A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm  
**Face plate material:** polycarbonate  
**Minimum wall box depth:** 35  
**Nature of supply:** AC  
**Rated fault current:** 30mA  
**Fixing screws:** 2 x M3.5