



## Technical Specification

ALF4747WHW-FO - 25A 2G DP Vertical Switch Indicator Flex



### General

**Box quantity:** 5  
**Total gross weight (g) includes packing:** 1735.00  
**Total net weight (g) excluding packaging:** 1533.00  
**Individual unit weight (g):** 307.00  
**Width mm:** 145.00  
**Height mm:** 95.00  
**Depth mm:** 20.00  
**Size/Dimensions (mm):** 145X95X20  
**Surf area M<sup>2</sup>:** 0.037

### Technical

**ABC indicator:** A  
**Insert colour:** white  
**Face plate finish:** moulded  
**Rocker finish:** red moulded  
**With indicator lamp:** yes  
**Number of rockers:** 1  
**Associated standards:** BS EN 60669-1  
**Rated voltage:** 220-250V  
**Rated current:** 45A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 2 x 4mm 1 x 6mm 1 x 10mm  
**Face plate material:** polycarbonate  
**Minimum wall box depth:** 47  
**Nature of supply:** AC  
**Fixing screws:** 2 x M3.5