



## Technical Specification

CLA3469WS - 13A Key Switched FCU DP Flex Outlet



### General

**Box quantity:** 1  
**Total gross weight (g) includes packing:** 170.00  
**Total net weight (g) excluding packaging:** 168.00  
**Individual unit weight (g):** 168.00  
**Width mm:** 85.00  
**Height mm:** 85.00  
**Depth mm:** 45.00  
**Size/Dimensions (mm):** 85X85X45  
**Surf area M<sup>2</sup>:** 0.030

### Technical

**ABC indicator:** A  
**Colour:** White  
**Insert colour:** white  
**Face plate finish:** metal  
**With indicator lamp:** Yes  
**Security features:** key activated  
**Security key type:** identical  
**Associated standards:** BS 1363-4  
**Rated voltage:** 220-250V  
**Rated current:** 13A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm  
**Face plate material:** steel  
**Nature of supply:** AC  
**Fixing screws:** 2 x M3.5  
**Mounting method:** surface