



## Technical Specification

SRA4824 - 20A 2G Double Pole Switch IP66



### General

**Box quantity:** 1  
**Total gross weight (g) includes packing:** 372.00  
**Total net weight (g) excluding packaging:** 298.00  
**Individual unit weight (g):** 298.00  
**Width mm:** 95.00  
**Height mm:** 95.00  
**Depth mm:** 75.00  
**Size/Dimensions (mm):** 95X95X75  
**Surf area M<sup>2</sup>:** 0.047

### Technical

**ABC indicator:** A  
**Colour:** Grey  
**Insert colour:** grey  
**Face plate finish:** moulded  
**Rocker finish:** grey  
**Number of rockers:** 2  
**Associated standards:** BS EN 60669-1  
**Rated voltage:** 220-250V  
**Rated current:** 20A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP66  
**Terminal capacity:** 3 x 1.5mm 2 x 2.5mm 1 x 4.0mm  
**Nature of supply:** AC  
**Type of cover:** grey polypropylene  
**Material housing:** grey polypropylene  
**Mounting method:** surface  
**Suitable for outdoor use:** yes