



## Technical Specification

LXR6356BBW - 2 Gang 13A DP Switched Socket + USB 5v/4800mA BB White Insert Plastic Rocker

# CONTACTUM



## AWAITING IMAGE

### General

**Box quantity:** 1  
**Total gross weight (g) includes packing:** 324.00  
**Total net weight (g) excluding packaging:** 317.00  
**Individual unit weight (g):** 317.00  
**Width mm:** 145.00  
**Height mm:** 85.00  
**Depth mm:** 30.00  
**Size/Dimensions (mm):** 145X85X30  
**Surf area M<sup>2</sup>:** 0.038

### Technical

**ABC indicator:** B  
**Insert colour:** white  
**Face plate finish:** brushed brass  
**Rocker finish:** white moulded  
**Number of rockers:** 2  
**Number of outlets:** 2  
**Number of socket outlets switchable:** 2  
**Associated standards:** BS 1363-2 2016+A1:2018  
**Rated voltage:** 220-250V  
**Rated current:** 13A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**With built-in USB power supply:** yes  
**Terminal capacity:** 3 x 2.5mm 2 x 4.0mm 2 x 6.0mm  
**Face plate material:** high grade electro plated stainless steel  
**Surface protection:** lacquered  
**Minimum wall box depth:** 35  
**Nature of supply:** AC  
**Fixing screws:** 2 x M3.5