
CONTACTUM



Technical Specification

LYR3457BSW - 45A DP Sw RR+13A Neon BS White Insert Plastic Rocker



General

 $\ \, \textbf{Box quantity:} \ 1$

Total gross weight (g) includes packing: 307.00 Total net weight (g) excluding packaging: 300.00

Individual unit weight (g): 300.00

Width mm: 145.00 Height mm: 85.00 Depth mm: 35.00

Size/Dimensions (mm): 145X85X35

Surf area M^2: 0.041

Technical

ABC indicator: B **Insert colour:** white

Face plate finish: brushed steel Rocker finish: white moulded With indicator lamp: yes Number of rockers: 2 Number of outlets: 1

Number of socket outlets switchable: $\boldsymbol{1}$

Associated standards: BS 4177 Rated voltage: 220-250V Rated current: 45A Frequency: 50-60Hz Wiring system: 2 pole

Ambient operating temperature:

Min. switch contact gap: 3mm

-5 to 40°C (24hour average not exceeding 25°C)

Degree of protection: IP2X

Terminal capacity: 2 x 4mm 1 x 6mm 1 x 10mm **Face plate material:** high grade stainless steel

Surface protection: lacquered Minimum wall box depth: 47

Nature of supply: AC Fixing screws: 2 x M3.5

