



## Technical Specification

DDS14166ASPMS - 14Way 63A Consumer Unit ISO Incomer + 2 RCD + SPD



### General

**Box quantity:** 1  
**Total gross weight (g) includes packing:** 6550.00  
**Total net weight (g) excluding packaging:** 6187.00  
**Individual unit weight (g):** 6187.00  
**Width mm:** 474.00  
**Height mm:** 260.00  
**Depth mm:** 130.00  
**Size/Dimensions (mm):** 474X260X130  
**Surf area M<sup>2</sup>:** 0.437

### Technical

**ABC indicator:** B  
**Colour:** White  
**Security features:** optional security lock available  
**Associated standards:** BS EN 61439-3  
**Rated voltage:** 220-250V  
**Rated current:** 63A  
**Frequency:** 50-60Hz  
**Wiring system:** 2 pole  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP4X  
**Width in number of modular spacings:** 22  
**Nature of supply:** AC  
**Rated fault current:** 30mA  
**DIN-rail:** yes  
**Extension possible:** yes  
**Type of cover:** steel  
**Type of door:** steel  
**Material housing:** steel  
**Plate thickness cabinet:** 1.2  
**Plate thickness door/cover:** 1.2  
**Mounting method:** surface  
**Number of outgoing ways:** 14