



## Technical Specification

X2752 - 1 Gang 2W 10AX Architrave Switch



### General

**Box quantity:** 20  
**GTIN-13 / EAN:** 5056199077106  
**Total gross weight (g) includes packing:** 884.00  
**Total net weight (g) excluding packaging:** 803.00  
**Individual unit weight (g):** 40.00  
**Width mm:** 30.00  
**Height mm:** 85.00  
**Depth mm:** 20.00  
**Size/Dimensions (mm):** 30X85X20  
**Surf area M<sup>2</sup>:** 0.010

### Technical

**ABC indicator:** A  
**Colour:** White  
**Face plate finish:** moulded  
**Rocker finish:** white moulded  
**Number of rockers:** 1  
**Associated standards:** BS EN 60669-1  
**Rated voltage:** 220-250V  
**Rated current:** 10AX  
**Frequency:** 50-60Hz  
**Wiring system:** 1 pole  
**Min. switch contact gap:** 3mm  
**Ambient operating temperature:**  
-5 to 40°C (24hour average not exceeding 25°C)  
**Degree of protection:** IP2X  
**Terminal capacity:** 3 x 1.0mm 3 x 1.5mm 1 x 2.5mm

**Face plate material:** thermoset

**Minimum wall box depth:** 25

**Nature of supply:** AC

**Fixing screws:** 2 x M3.5



**CONTACTUM**

Make The Switch 

---