

Technical Specification

REF4900BSW - 2 Gang 13A Latching Socket DP White





General

Box quantity: 1 GTIN-13 / EAN: 5056199066278 Total gross weight (g) includes packing: 332.00 Total net weight (g) excluding packaging: 278.00 Individual unit weight (g): 278.00 Width mm: 145.00 Height mm: 85.00 Depth mm: 35.00 Size/Dimensions (mm): 145X85X35 Surf area M^2: 0.041

Technical

ABC indicator: A Insert colour: white Fault current protection (RCD): 30mA Face plate finish: brushed steel Rocker finish: white moulded Number of rockers: 2 Number of outlets: 2 Number of socket outlets switchable: 2

Associated standards: BS7288: 2016 & BS 1363-2: 2016 +A1: 2018 Rated voltage: 220-250V Rated current: 13A Frequency: 50-60Hz Wiring system: 2 pole Min. switch contact gap: 3mm

Ambient operating temperature: -5 to 40°C (24hour average not exceeding 25°C) Degree of protection: IP2X Terminal capacity: 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm Face plate material: high grade stainless steel Surface protection: lacquered Minimum wall box depth: 35 Nature of supply: AC Rated fault current: 30mA Fixing screws: 2 x M3.5

RCD Type: Type A

