



Technical Specification

REF4900PSB - 2 Gang 13A Latching RCD Socket DP



General

Box quantity: 1
GTIN-13 / EAN: 5056199066322
Total gross weight (g) includes packing: 332.00
Total net weight (g) excluding packaging: 278.00
Individual unit weight (g): 278.00
Width mm: 145.00
Height mm: 85.00
Depth mm: 35.00
Size/Dimensions (mm): 145X85X35
Surf area M²: 0.041

Technical

ABC indicator: A
Insert colour: black
Fault current protection (RCD): 30mA
Face plate finish: polished steel
Rocker finish: black moulded
Number of rockers: 2
Number of outlets: 2
Number of socket outlets switchable: 2
Associated standards:
BS7288: 2016 & BS 1363-2: 2016 +A1: 2018
Rated voltage: 220-250V
Rated current: 13A
Frequency: 50-60Hz
Wiring system: 2 pole
Min. switch contact gap: 3mm
Ambient operating temperature:
-5 to 40°C (24hour average not exceeding 25°C)
Degree of protection: IP2X
Terminal capacity: 3 x 2.5mm 3 x 4.0mm 2 x 6.0mm
Face plate material: high grade stainless steel
Minimum wall box depth: 35
Nature of supply: AC
Rated fault current: 30mA
Fixing screws: 2 x M3.5

RCD Type: Type A